SULZER

Sulzer Mixpac

# Pneumatic MIS Dispenser TS493X

2-K 600 ml 1:1 Cartridge

**Suitability**

- Force 4 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min.
- 2-Component Cartridge, 600 ml
- Material Viscosity High
- Professional Use

| [mm] | 1:1 |
|---|---|
| a | 217.0 |
| b | 102.0 |
| c | 51.0 |
| | |




| Part Number | Article | Description | Packaging |
|---|---|---|---|
| **DP2 600-40-100** | 151790 | Weigth 2.58 kg, Length 535 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading | 1 unit |

| Product advantages | Customer benefits |
|---|---|
| Air operated plunger retraction | Quick cartridge exchange |
| One hand pressure adjustment | Simple dispensing speed adjustment, also during working |
| Centered handle | Well balanced dispneser for precise working |
| AntiDrip | Clean application |


**Headquarters**

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

**Denmark**

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

**USA, South America, Canada and Mexico**

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

**UK and Ireland**

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

**Asia Pacific**

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com


Vers. 1.6 2014